

## FLOOR MAT SYSTEM

### CROSS REFERENCE TO RELATED APPLICATION

5 This application is a continuation-in-part application claiming priority from U.S. Patent 6,352,757 dated March 5, 2002, which is a continuation-in-part application of U.S. Patent 6,042,915 dated March 28, 2000, which is a continuation application of U.S. Patent 5,958,538 dated September 28, 1999, the disclosures of these references are incorporated herein by reference.

### BACKGROUND OF THE INVENTION

#### Technical Field

10 The present invention generally relates to a floor mat system and, more particularly, to a floor mat system designed to include a plurality of floor mats disposed next to each other in a manner that prevents the mats from riding up onto each other.

#### Background Information

15 Floor mats are often used at the entrances of businesses for customers to wipe water and snow from the bottoms of their shoes. Conventional floor mats are constructed of a flexible rubber and are formed with a plurality of spaced apart orthogonal ribs which form rectangular-shaped openings. These conventional floor mats require that a recessed area be formed in the floor where the floor mats are located with the edges of the recessed area preventing the floor mats from sliding when walked upon by a customer. The water and snow from the customer's shoes flows through the openings keeping the top surface of the floor mat free of standing water.

20 Although these prior art floor mats are adequate for the purpose for which they were intended, the business owner must plan for the installation of these

floor mats and have the recessed area built into the floor during construction of the building. If these prior art floor mats are merely placed on the floor without a recessed area the floor mats slide when a horizontal pressure from a customers shoes or from strong wind is applied on the mats. Alternatively, the recessed area can be dug out of the floor after the building has been constructed at a great expense to the business owner. Additionally, even when a recessed area has been provided to accept the floor mat, if large mats are utilized, or a number of mats are utilized adjacent one another, the mats may still move within the recessed area possibly causing an unsafe condition.

Another type of floor mat merely sits on the floor allowing the water and snow from the customers' shoes to flow through the openings. Unless these floor mats are surrounded by some type of frame, the water will eventually build up beneath the floor mat and flow back out into the traffic area creating a puddle of water in front of the floor mat where the customers step. If the floor mat is placed within the business owner's store, the water will eventually flow out into the aisles or walkways creating a slippery and hazardous condition.

Also, if the area to be covered by the floor mats is a relatively large area such as the entrance or exit to a supermarket, a plurality of these floor mats must be placed at the entrance way to collect the snow and water from customer's shoes. If each of these plurality of floor mats is contained within its own separate frame, the front floor mats which the customers walk upon first will collect a majority of snow and water while the floor mats closer to the door will be relatively dry. Eventually, the front floor mats will fill with water causing an overflow of water into the walkway or causing standing water on the top surface of the mat.

Therefore, the need exists for an improved floor mat system having inner and outer frame members which extend between and around, respectively, a plurality of floor mats, which frame members attach directly to the floor to restrict movement of the floor mats, in which the frame members include a seal

receiving recess formed in a bottom end thereof for selectively receiving a seal and which the mats are easily removable from within the frame to allow the water under the mat to be cleaned up and which are easily placed back in the frame.

5 Floor mats are also used between the storage areas in retail establishments and the display or retail environment of the retail establishment. These floor mats are intended to prevent dirt, water, and other debris from entering the retail environment from the storage environment where goods are unloaded from trucks. These floor mats are subjected to foot traffic as well as traffic from wheeled transport vehicles such as loaders or pull carts that are used to move goods from the storage area to the retail environment of the store. These transport vehicles are typically very heavy and include relatively small wheels in order to keep the height of the transport vehicle low. These transport vehicles typically have three or four wheels.

10 A problem has occurred in the art when these transport vehicles are rolled over prior art floor mats. It has been found that the movement of the transport vehicle over the floor mat causes the floor mat to "creep" or move out of its intended location. This movement is believed to occur when the wheels of the transport vehicle engage the floor mat under a heavy load. The floor mats must be manually repositioned after such movement. One solution has been to fasten the floor mat to the floor with clips to prevent the mats from moving. Although this is functional, the clips prevent the mats from being readily pulled up during cleaning. It is thus desired in the art to provide a floor mat system for use with relatively heavy, wheeled transport vehicles that will allow the transport vehicle to be rolled over the floor mat system without moving the floor mat system.

25 Another problem with prior art floor mat systems is that the rib structure of the floor mats is designed to support foot traffic and is not designed to carry the relatively heavy point loads created by a wheeled transport vehicle. Prior art

rib structures allow the point load of a small wheel to depress the floor mat between ribs eventually causing damage to the floor mat and allowing the wheel to obtain a better grip on the floor mat to move the floor mat. One solution to this problem has been to create floor mats with ribs that are closely adjacent. The problem with floor mats having closely adjacent ribs is that there is little room for the floor mat to collect debris and little room for the liquid under the floor mat to flow. Another solution has been to provide a floor mat having intersecting ribs. The problem with floor mats having intersecting ribs is that the intersecting ribs prevent liquid from flowing under the floor mat to a drain positioned in one area of the floor mat. As such, it is desired in the art to provide a floor mat structure that is capable of supporting relatively heavy rolling point loads while maintaining liquid flow channels and room for debris under the floor mat.

Another problem in the art of floor mat systems is when the edges of adjacent mats ride up over each other to create a tripping hazard. The prior art recognizes that one solution to this problem is to place the adjacent floor mats in individual wells defined by frame members. The drawback with this solution is the cost of fabricating and installing the frame members. The art desires a floor mat system that includes a plurality of mats disposed in an edge-to-edge - or abutting - relationship wherein the risk of edge creep (wherein the edges ride up over each other during normal use) is eliminated.

### **SUMMARY OF THE INVENTION**

The invention provides a floor mat system having a plurality of floor mats disposed in edge-to-edge relationships. The floor mats are held in place with clips that prevent the mats from creeping over each other while allowing the mats to be lifted from the floor.

One embodiment of the invention provides that each floor mat is held down with four clips disposed at the corners of the floor mat. Another

embodiment provides mats held in place with clips positioned at the centers of the mats.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

5 The preferred embodiments of the invention, illustrative of the best modes in which applicant has contemplated applying the principles of the invention, are set forth in the following description and are shown in the drawings and are particularly and distinctly pointed out and set forth in the appended claims.

Fig. 1 is a top plan view of the floor mat system of the present invention.

Fig. 2 is an exploded perspective view of the floor mat system of Fig. 1.

Fig. 3 is a fragmentary top plan view of the floor mat system of Fig. 1 with portion broken away.

Fig. 4 is a fragmentary sectional view taken along line 4-4, Fig. 3.

Fig. 5 is a top plan view of a second embodiment of the floor mat system of the present invention.

Fig. 6 is a top plan view of a third embodiment of the floor mat system of the present invention showing a rolling load being applied to the floor mat system.

Fig. 7 is a sectional side view of a portion of one of the floor mats of the system of the third embodiment.

Fig. 8 is a sectional view similar to Fig. 7 showing a fourth embodiment of the floor mat.

Fig. 9 is a bottom plan view taken along line 9-9 of Fig. 7.

Fig. 10 is a view similar to Fig. 9 taken along line 10-10 of Fig. 8.

Fig. 11 is a view similar to Fig. 9 showing a fifth embodiment of the floor mat.

Fig. 12 is a view similar to Fig. 9 showing a sixth embodiment of the floor mat.

Fig. 13 is a view similar to Fig. 9 showing a seventh embodiment of the floor mat.

Fig. 14 is a view similar to Fig. 9 showing an eighth embodiment of the floor mat.

5 Fig. 15 is a view similar to Fig. 6 showing the rolling load disposed in the middle of the floor mat system.

Fig. 16 is a sectional view taken along line 16-16 of Fig. 15.

Fig. 17 is a view similar to Fig. 6 showing an alternative configuration of the floor mat system of the present invention.

Fig. 18 is a sectional view taken along line 18-18 of Fig. 17.

Fig. 19 is a perspective view of a clip used with the floor mat system of the present invention.

Fig. 20 is a sectional view of the clip holding the floor mat to the ground.

Fig. 21 is a sectional view taken along line 21-21 of Fig. 20.

15 Fig. 22 is a top plan view of a mat system according to an alternative embodiment of the invention.

Fig. 23 is an enlarged top plan view of the encircled portion of Fig. 22.

Fig. 24 is a section view taken along line 24-24 of Fig. 23.

20 Fig. 25 is a top plan view of a further alternative embodiment of a floor mat system according to the present invention.

Fig. 26 is a top plan view of still a further embodiment of a floor mat system according to the concepts of the present invention.

Similar numerals refer to similar parts throughout the specification.

25

### **DESCRIPTION OF THE PREFERRED EMBODIMENTS**

The floor mat system of the present invention is shown in Fig. 1 and is indicated generally at 1. System 1 is shown in Figs. 1-4 positioned directly on a floor 4. However, system 1 can be positioned within a recessed area which is formed in floor 4 without departing from the spirit of the present invention.

Floor 4 may be constructed of various materials, such as wood or blacktop, and is shown in Figs. 1-4 constructed of cement.

System 1 includes a plurality of floor mats, indicated generally at 8, and a frame assembly, indicated generally at 10 (Fig. 2), which extends around and between floor mats 8. In the preferred embodiment, floor mats 8 are 4 foot by 4 foot but may be various sizes without affecting the concept of the invention. Floor mats 8 include a series of first parallel rectangular-shaped ribs 14 (Fig. 4) which are spaced apart from one another by a distance substantially equal to their width, or approximately 1/4 inches. A series of second spaced parallel rectangular-shaped ribs 17 extend perpendicular to and between first ribs 14 forming rectangular openings 20 therebetween.

In accordance with one of the features of the invention, second ribs 17 consist of a pair of middle ribs 18 which extend between a pair of support ribs 18a. Middle ribs 18 are approximately 1/8 inches wide and are separated from one another by a distance which is approximately 5/16 inches. Support ribs 18a have an enlarged bottom 21 which forms an upwardly facing shoulder 24 on each side of support ribs 18a. Support ribs 18a are spaced apart from adjacent middle ribs 18 by a distance of approximately 3/8 inches. Additionally, second ribs 17 are slightly shorter than first ribs 14 thereby creating a sculptured top surface of floor mat 8. Additionally, enlarged bottom 21 extends substantially below the bottom surface of first ribs 14 and of middle ribs 18 thereby suspending the majority of floor mat 8 above floor 4 thereby creating drainage channels 26 for water and debris scraped from customer's shoes.

Frame assembly 10 includes inner frame members 30 and outer frame members 32 which extend between and around, respectively, floor mats 8 as described below. Inner frame members 30 are elongated rectangular shaped members formed with a generally U-shaped seal receiving recess 36 in the bottom thereof. Inner frame members 30 include a top surface 38 which is formed with a pair of spaced parallel raised projections 40 extending the entire

length of inner frame members 30 and a pair of opposed sidewalls 42 having a bottom end 44 positioned on each side of recess 36.

Outer frame members 32 are elongated and generally triangular shaped in cross-section. Outer frame members 32 have an inner sidewall 48, and angled top surface 50 which is tapered downwardly away from sidewall 48 and which includes a plurality of raised projections 52 formed along the entire length thereof, and a bottom end 54. Bottom end 54 is formed with a seal receiving recess 58 which includes a generally U-shaped section 60 formed adjacent sidewall 48, a generally triangular shaped section 62 formed at an angle similar to that of top surface 50 and a middle gap 64 which extends between and connects sections 60 and 62. Inner and outer frame members 30 and 32, respectively, are secured to floor 4 by a plurality of screws 68 which extend through the frame members and into floor 4.

In accordance with one of the main features of the invention, inner and outer frame members 30 and 32, respectively, may optionally and selectively receive a seal 70 and 72, respectively. Seal 70 is a generally tubular shaped member having a center hole 74 and is formed of a resilient material such as rubber. Seal 70 may be positioned within U-shaped seal receiving recess 36 and is sandwiched between inner frame member 30 and floor 4. The downward pressure of inner frame member 30 causes seal 70 to deform to the oval shape shown in Fig. 4 creating a watertight seal between inner frame member 30 and floor 4.

Seal 72 of outer frame member 32 is a generally flat piece of resilient material such as rubber, having first and second sides 76 and 78 and a flat intermediate section 80 extending between sides 76 and 78. Side 76 extends within U-shaped section 60 of seal receiving recess 58, flat intermediate section 80 is sandwiched within gap 64 of seal receiving recess 58 and side 78 extends within triangular shaped section 62 of seal receiving recess 58. Seal 72 is



sandwiched between outer frame member 32 and floor 4 creating a watertight seal between outer frame member 32 and floor 4.

When assembled, outer frame members 32 are attached to floor 4 defining a periphery of an area which floor mat system 1 is to cover. Outer frame members 32 have one of floor mats 8 adjacent to and abutting inner sidewall 48 thereof. Inner frame members 30 divide the area to be covered by floor mat system 1 into four by four foot wells 90 (Fig. 3). Inner frame members 30 have a floor mat 8 adjacent to and abutting each sidewall 42 thereof. Each well 90 receives one of floor mats 8 and prevents floor mats 8 from sliding or otherwise moving when walked upon by a customer. Outer frame members 32 and inner frame members 30 offer an additional benefit in that they are of consistent cross section and therefore are extrudable thereby substantially reducing manufacturing costs for floor mat system 1.

In the preferred embodiment, inner frame members 30 have a height of approximately 7/16 inches measured from top surface 38 to bottom ends 44 with projections 40 extending approximately 1/16 inches above top surface 38. Inner frame members 30 have a width of approximately 3/4 inches with bottom ends 44 being 1/8 inches wide and seal receiving recess 36 being 1/2 inch wide. Similarly, outer frame members 32 have a height of approximately 1/2 inches measured from the top to the bottom of inner side wall 48. Outer frame members 32 have a width of approximately 1 1/2 inches measured from inner side wall 48 to the outer tip or edge of frame member 32. Thus, outer frame members 32 have a height substantially equal to the height of inner frame members 30 measured from the top of projections 40 to bottom ends 44, or approximately 1/2 inches. Floor mats 8 are supported by support ribs 18a at a height of approximately 7/16 inches to allow floor mats 8 to sit relatively even with the top surface of inner frame members 30 creating a substantially flat floor mat system 1 with a sculptured top surface for scraping water and debris from customer's shoes. Projections 40 of inner frame members 30 and the top of

outer frame members 32 are slightly higher than floor mats 8 to create additional scraping edges to scrape water and debris from customer's shoes. Top surface 50 of outer frame members 32 are ramped to prevent customers from tripping when stepping from floor 4 onto floor mat system 1.

5 As the water and debris is scraped from the customer's shoes, it flows through openings 20 into drainage area 26 under floor mats 8. In a large area covered by a plurality of four by four foot floor mats 8, the front most floor mats will tend to accumulate a majority of the water and debris from the customer's shoes, eventually creating an overflow condition. By selectively inserting optional seals 70 and 72 within inner and outer frame members 30 and 32, 10 respectively, the water and debris can be evenly distributed beneath floor mat system 1. For example, in the floor mat system of Fig. 1 where floor mats 8a are the front most floor mats which tend to collect a majority of the water and debris, and floor mats 8b are the back most floor mats which remain relatively dry, seal 70 may be removed or excluded from inner frame members 30 extending between floor mats 8a and 8b allowing the water and debris to flow in the direction of arrows A creating an even distribution of the water and debris under floor mat system 1. Floor mats 8a and 8b will eventually have to be removed from wells 90 allowing the water and debris to be cleaned from wells 90. Floor 15 mats 8a and 8b are placed back within wells 90 for subsequent reuse.

Also, because floor 4 will not be perfectly flat and support ribs 18a will not lay perfectly flat on floor 4, there will be some leakage between drainage areas 26 which are formed between support ribs 18a. This leakage between drainage areas 26 allows a floor drain 96 (Fig. 3) to be formed under one of floor mats 8. Drain 96 provides for removal and drainage of water and debris from beneath floor mats 8. Seal 70 may be optionally inserted within any of inner frame members 30 to selectively create a desired flow of water to the area of drain 96. Further, seal 72 may be left out of a portion of one of outer frame members 32 in the event a drain is located outside or adjacent to floor mat system 1. The 25

water or debris may be directed toward one side or end of floor mat system 1 creating a flow to an outer drain 96. Alternatively, floor mats 8 may be removed from wells 90 allowing the debris to be hosed from wells 90 with a water hose with the directional flow allowing the clean water to exit frame assembly 10 as described above.

A second embodiment of the floor mat system of the present invention is indicated at 100 in Fig. 5 and shows six four by four foot floor mats contained within outer frame members 32 and is separated from one another by inner frame members 30. Floor mat system 100 shows that the floor mat system of the present invention may be used to cover any sized area with outer frame members 32 defining the periphery thereof. Any number of inner frame members 30 necessary to divide the area to be covered into four by four foot wells 90 may be included within outer frame members 32. Seals 70 and 72 may be optionally included within seal receiving recesses 36 and 58 of inner and outer frame members 30 and 32, respectively, to direct and disperse the flow of water and debris within drainage areas 26 beneath floor mats 8.

It is understood that floor mat system 1 may be placed within a recessed area formed in floor 4. In such an embodiment, the periphery of floor mat system 1 may be defined by the edges of the recessed area or alternatively, inner frame members 30 may be inserted within the recessed area around the edge thereof to define the periphery of the area to be covered by floor mats 8. Inner frame members 30 will thus have a floor mat 8 adjacent and abutting only one side thereof.

Also, inner frame members 30 may be cut in any manner which allows the inner frame members to form the four by four foot wells 90. For example, Fig. 5 shows one piece inner frame members 30 extending transversely between the longer outer frame members 32 and are of a length substantially equal to the eight foot length of two of floor mats 8 plus the width of the inner frame member extending between the two floor mats 8. For example, inner frame members 32

which extend longitudinally between the floor mats are cut into four foot sections and extend between the shorter outer frame members 32 and the one piece inner frame members 30, and between the one piece inner frame members. Further, it is understood that in the preferred embodiment, floor mats 8 and wells 90 are four foot by four foot but may be other square or rectangular shapes such as three by three foot or three by five foot without affecting the concept of providing a frame assembly having selectively insertable seals to direct and evenly disperse the flow of water beneath the mats.

Accordingly, floor mat systems 1 and 100 include a plurality of floor mats 8 and a frame assembly 10. Frame assembly 10 include inner and outer frame members 30 and 32, respectively, which are formed with seal receiving recesses 36 and 58, respectively. Outer frame members 32 define a periphery of an area to be covered by floor mat system 1 and inner frame members 30 divide the area into four by four foot wells 90. Floor mats 8 are four by four foot in size and are received within wells 90 to prevent any sliding movement thereof. A drainage area 26 is formed beneath floor mats 8 to allow water and debris to flow through openings 20 formed by ribs 14 and 17 of floor mat 8. Seals 70 and 72 may be optionally and selectively inserted within seal receiving recesses 36 and 58, respectively, to direct and disperse the water and debris which accumulates within drainage area 26. Drain 96 may be formed beneath floor mats 8 or adjacent floor mat systems 1 or 100 allowing seals 70 and 72 to be selectively inserted within inner and outer frame members 30 and 32, respectively, to direct the flow of water and debris towards the drain.

A third embodiment of the floor mat system of the present invention is indicated generally by the numeral 200 in Fig. 6. Floor mat system 200 is intended to be used in areas that support heavy load traffic such as that created by pull carts, loaders, or other transport vehicles 202. Transport vehicle 202 is typically used to move inventory from an area such as a storeroom or loading dock 204 to a showroom or retail environment 206. In the example of the

invention depicted in Fig. 6, floor mat system 200 is installed in a hallway 208 disposed between doors 210. Transport vehicle 202 thus necessarily passes over floor mat system 200 as it moves from stockroom 204 to showroom 206. Floor mat system 200 is intended to remove water and debris from the wheels 212 of transport vehicle 202 before the water or debris enters showroom 206. Floor mat 200 thus helps keep showroom 206 clean. Of course, floor mat system 200 may be used in any of a variety of locations and the position of system 200 is not to be limited to a location between walls. System 200 may be positioned in the middle of an open area where transport vehicle 202 or persons walking over system 200 may cross it in any direction.

Although the structure and configuration of the floor mat systems described above with respect to the first and second embodiments of the invention have been useful for their intended purposes, problems have occurred with their use when combined with relatively heavy rolling loads such as that created by transport vehicle 202. These problems are discussed above in the Background of the Invention section of this specification. In response to these problems, floor mat system 200 has been developed which includes a plurality of individual floor mats 214 arranged in a grid pattern within a frame system 216 including an outer frame 218 and at least one inner frame member 220. Outer frame 218 and inner frame members 220 can be either rigid, flexible, or semi-flexible depending upon the specific needs of the particular application. In this regard, outer frame 218 and inner frame members 220 can be made of any one of a variety of materials including aluminum, steel, rubber, plastic, as well as a variety of other materials without departing from the spirit of the present invention.

Each floor mat 214 is similar to the floor mats described above. In the preferred embodiment of the present invention, each floor mat 214 includes a series of spaced, substantially parallel, first rectangular-shaped ribs 222 which are spaced apart from one another by a distance substantially equal to their

width. In the embodiment depicted in the drawings, the width is approximately one-quarter inch. In other embodiments of the invention, different widths and different spacing may be used without departing from the concepts of the present invention. A series of second spaced, parallel, rectangular-shaped ribs 224 extend substantially perpendicular to and between first ribs 222 forming rectangular openings 226 therebetween.

Second ribs 224 include support ribs 228 and may optionally include middle ribs 230. In the embodiment of the invention depicted in the drawings, middle ribs 230 are disposed in pairs and are approximately one-eighth inch wide and are separated from one another by a distance from about one-eighth to three-eighths inch and preferably five-sixteenths inch. Support ribs 228 have an enlarged bottom 232 that forms an upwardly facing shoulder 234 on each side of support ribs 228. The lower most surface of each support rib 228 is substantially planar and is intended to support floor mat 214 on the floor 236. Support ribs 228 are spaced apart from the closest adjacent middle rib 230 by distance of approximately three-eighths inch. Second ribs 224 are slightly shorter than first ribs 222 thereby creating a sculptured top surface on floor mat 214. Support ribs 228 support middle ribs 230 and first ribs 222 above floor 236 thereby creating drainage channels or liquid flow channels 238 for water and debris scraped from shoes or wheels 212 above.

In accordance with one of the objectives of the present invention, floor mat 214 further includes a plurality of support knobs 240 that extend down from the lower surface of first ribs 222 and engage floor 236 to provide additional support to floor mat 214. In the embodiment of the invention depicted in Fig. 7, each support knob 240 is conical with its wider base connected to the lower surface of each first rib 222 and is disposed substantially centrally between support ribs 228. Each support knob 240 is substantially the same height as enlarged bottom 232 of support ribs 228 so that support knobs 240 work in cooperation with support ribs 228 to provide support to floor mat 214.

Support knobs 240 also allow drainage channels 238 to remain substantially open. Support knobs 240 are not large enough to block the flow of water within drainage channels 238 and are not large enough to prevent debris from gathering under floor mat 214. However, support knobs 240 provide extra support to floor mat 214 such that the relatively heavy point loads created by wheels 212 of transport vehicle 202 do not cause ribs 222 or 230 to collapse between support ribs 228 when transport vehicle 202 is rolled across floor mat 214.

A fourth embodiment of the floor mat system of the present invention is indicated generally by the numeral 242 in Fig. 8. Floor mat system 242 includes many of the same elements as floor mat system 200 described above. However, floor mat system 242 includes a plurality of floor mats 244 that differ from floor mats 214 in that they include a plurality of support knobs 246 that are smaller than support knobs 240. Each support knob 246 is conical but disposed on middle rib 230 between first ribs 222 as shown in Fig. 10. The configuration of Fig. 8 provides even more points of support to floor mat 244 without clogging drainage channels 238.

A fifth embodiment of the floor mat system of the present invention is indicated generally by the numeral 248 in Fig. 11. System 248 includes floor mats 250 having substantially the same elements as floor mats 214 described above except that the support knobs 252 of floor mat 250 are of a substantially rectangular parallelepiped configuration. In the preferred embodiment of the invention, support knobs 252 have a square cross-section. Support knobs 252 are disposed in substantially the same location with respect to ribs 222 and 224 as support knobs 240.

A sixth embodiment of the floor mat system is indicated generally by the numeral 254 in Fig. 12. System 254 includes a plurality of floor mats 256 that have many of the same elements as floor mats 214. The support knobs 258 of floor mat 256 have the same cross-sectional shape as support knobs 252 but

are substantially smaller than support knobs 252. Support knobs 258 are disposed in substantially the same location with respect to ribs 222 and 224 as support knobs 246.

A seventh embodiment of the floor mat system of the present invention is indicated generally by the numeral 260 in Fig. 13. System 260 includes a plurality of floor mats 262 having many of the same elements as floor mats 214 described above. The support knobs 264 of system 260 are substantially cylindrical in shape and are disposed in the same location with respect to ribs 222 and 224 as support knobs 240.

Fig. 14 depicts an eighth embodiment of the system of the present invention. The eighth embodiment of the system is indicated generally by the numeral 266. System 266 includes a plurality of floor mats 268 that are substantially the same as floor mats 214 described above. Floor mats 268 include support knobs 270 that are cylindrical and are disposed in substantially the same location with respect to ribs 222 and 224 as support knobs 246.

Having now described the various structures of the floor mats capable of being used with the floor mat system of the present invention, the manner in which the floor mat system is used to support a heavy load without allowing individual floor mats 214 to move up and out of frame system 216 will now be described. It has been found in the art that when transport vehicle 202 is rolled across prior floor mat grids, the individual floor mats are urged out from the frames where they can be tripped over or stop the wheels of the transport vehicle. System 200 of the present invention allows transport vehicle 202 to be rolled over floor mats 214 without allowing floor mats 214 to come up and out of frame system 216. This is accomplished without the use of clips or hold down devices that permanently lock the position of floor mats 214 with respect to floor 236, as will be set forth more fully below. Each floor mat 214 may be readily lifted up away from frame system 216 to allow debris to be cleaned from under system 200.



In accordance with one of the objectives of the present invention, each floor mat 214 has a length, indicated by a dimension line labeled by the numeral 280, and a width, indicated by the dimension line labeled by the numeral 282 (See Fig. 15). Floor mats 214 are arranged so that widths 282 are directed in the direction of travel for transport vehicle 202. As is understood in the relevant art, transport vehicle 202 includes four wheels at opposite corners thereof that are arranged into two pairs of spaced apart coaxial wheels, with each pair of wheels rotating about an imaginary axis, the two imaginary axes being parallel and spaced apart. The distance between the two imaginary axes constitutes a wheelbase distance indicated by the numeral 284. The distance by which each pair of coaxial wheels is separated defines a track distance indicated by the numeral 285. In accordance with one of the objectives of the present invention, length 280 and width 282 are sized such that any two wheels 212 of vehicle 202 cannot rest on a single floor mat 214 at any given time. In the preferred embodiment of the present invention, an entire width 282 (and thus an entire floor mat 214) is disposed between the floor mats 214a and 214b that together support a pair of wheels 212. It can be seen, therefore, that width 282 is less than wheelbase distance 284. Similarly, length 280 of each floor mat 214 is less than track distance 285 such that any pair of coaxial wheels, *i.e.*, the front wheels or the rear wheels, will never lie on a single floor mat 214, but rather will rest on two adjacent floor mats 214. It has been found as part of the present invention that the configuration of length 280 and width 282 in this manner prevents wheels 212 from working together to dislodge floor mat 214 from frame system 216.

Providing floor mats 214 in the manner discussed above insures that only one wheel of transport vehicle 202 will reside on a single floor mat 214 at a given time. This prevents two wheels 212 of transport vehicle 202 from working together to move floor mat 214. In the past, two wheels 212 present on floor mat 214 would cooperate to move mat 214 out of its desired location. This

problem forced workers to reposition floor mats because misplaced floor mats could trip those walking over the floor mat or jam wheels 212 of transport vehicle 202 as it was rolled over the floor mat. The arrangement of the present invention prevents these problems because wheels 212 cannot cooperate together to dislodge floor mat 214.

System 200 may be arranged by first selecting a location on a floor on which to install system 200. The person installing system 200 then selects floor mats 214 having the desired widths 282 in lengths 280 so that two wheels 212 of transport vehicle 202 cannot reside on a single floor mat 214 at any given time in the length-wise, width-wise, or diagonal directions. The person arranging system 200 then lays out the total number of floor mats 214 to fill the selected area. The elements and dimensions of frame 216 are then determined and installed.

In the preferred embodiment of the present invention, each floor mat 214 is preferably eighteen by twenty-four inches. However, in other embodiments of the invention, each floor mat 214 may be as small as eight by twelve inches to as large as twenty-four by thirty-six inches. Although it is desired that width 282 be directed in the intended direction of wheeled traffic, lengths 280 may also be sized to be less than wheelbase distance 284 such that traffic crossing in the length direction will also not dislodge floor mats 214. It is also desired to size floor mats 214 such that the diagonal length of each floor mat 214 is less than one of track distance 285 and wheelbase distance 284 so that diagonal traffic across system 200 will not dislodge floor mats 214.

An alternative embodiment of system 200 is depicted in Figs. 17 and 18 and is indicated generally by the numeral 300. System 300 includes many of the same elements as system 200 and similar numbers are referred to similar elements. System 300 is intended to be used with a transport vehicle 302 having a larger wheel base 384 than vehicle 202. The larger wheel base 384 allows floor mats 314 to have a width 382 that is larger than width 282 as

described above. The wheel configuration of vehicle 302 may also allow length 380 to be larger than length 280.

In accordance with another objective of the present invention, a clip 350 is depicted in Figs. 19-21. Clip 350 is intended to be used with floor mats 214 described above. The operation of clip 350 is similar to that of the clip disclosed in U.S. Patent No. 5,882,764, the disclosures of which are incorporated herein by reference.

Clip 350 includes a substantially rectangular body 352 and two pairs of ears 354 extending therefrom. Body 352 is a substantially rectangular parallelepiped-shaped member terminating at a pair of opposed ends 356 and at a pair of opposed sides 358. Body 352 is formed with a plurality of relief holes 360 that are sized and spaced apart to accommodate support knobs 240 therein. Body 352 is also formed with two fastening holes 362 that are each sized to accommodate a screw 364 therethrough for purposes of fastening clip 350 onto floor 236.

As is best shown in Fig. 19, ears 354 are each disposed adjacent ends 356 and protrude both upwardly from body 352 and outwardly beyond sides 358. The portion of each ear 354 that protrudes outward from body 352 beyond side 358 constitutes a latching ledge 366. Latching ledges 366 lockingly engage facing shoulders 234 of support ribs 228 to removably retain floor mat 214 against floor 236. Latching ledges 366 each are formed with a beveled lower surface that retains floor mat 214 against floor 236 during use, but permits floor mat 214 to be pulled upward and out of engagement with latching ledges 236 when it is desired to remove floor mat 214 from floor 236 for purposes of cleaning and for other such purposes. While clip 350 is shown with relief holes 360 that correspond with support knobs 240 of floor mat 214, it is understood that clip 350 and relief holes 360 can be reconfigured to cooperate with mat 244, mat 250, mat 256, mat 262, and mat 268.

An alternative floor mat system is depicted in Figs. 22-24 and is indicated generally by the numeral 400. Mat system 400 generally includes at least one but preferably a plurality of individual floor mats 214 as described above with respect to the third embodiment of the floor mat system of the invention. Floor mat 214 is depicted in Figs. 6-9 with alternative versions of floor mat 214 being depicted in Figs. 10-14. Any of the floor mat embodiments depicted in these drawings may be used with floor mat system 400. Floor mat system 400 is specifically used when more than one floor mats 214 must be used adjacent to each other to cover an area of the floor 4 that is larger than a single floor mat 214. Problems occurred in prior art systems when floor mats were positioned adjacent to each other in edge-to-edge or abutting relationships because adjacent floor mats would creep along the supporting surface of the floor and overlap each other creating a tripping hazard. The embodiments of the invention described above, and in this inventor's previous applications, have used inner frame members 30 and 220 to eliminate this problem. Floor mat system 400 has been found to eliminate this problem without the use of inner frame members. Floor mat system 400 is thus easier and less expensive to install than prior art systems. System 400 thus provides a significant improvement over prior art systems.

System 400 uses at least four clips 350 to hold each floor mat 214 in place in an abutting relationship with respect to the other floor mats 214 of system 400. The inventor has found that the combination of mats 214 with clips 350 will prevent the edges of adjacent mats 214 from creeping up on top of each other when installed in an abutting relationship. The use of clips 350 with mats 214 thus allows a plurality of mats 214 to be installed in abutting relationships as depicted in Fig. 22 without the use of interior frame members to prevent the edges of mats 214 from creeping over each other. The use of knobs 240 projecting down from mat 214 disposed within holes 360 of clip 350 in

combination with ears 354 and latching ledges 366 prevents floor mats 214 from moving enough to cause the edges to overlap.

System 400 uses four clips 350 disposed at the corners of mats 214. Fig. 23 shows adjacent edges 402 that are closely adjacent (small space separating them) or engaged with each other. In one embodiment of the invention, each clip 350 receives eight of the knobs with the longitudinal edges of clip 350 engaging opposed ribs of mat 214 so that mat 214 is tightly held in place.

Fig. 25 shows an alternative embodiment of system 400 wherein outer frame members 32 are disposed around the common perimeter of the plurality of mats 214. No portion of outer frame member 32 extends below any portion of mats 214.

Fig. 26 depicts an alternative system 450 wherein each floor mat 214 is attached to floor 4 with a single clip 350. Floor mats 214 are substantially smaller in width and length than mats 214 shown in system 400 such that only a single clip 350 may be used with each floor mat 214. As shown in the drawing, each floor mat 214 in this embodiment has a length that is less than twice the length of clip 350.

Accordingly, the improved floor mat system is simplified, provides an effective, safe, inexpensive, and efficient device which achieves all the enumerated objectives, provides for eliminating difficulties encountered with prior art devices, and solves problems and obtains new results in the art.

In the foregoing description, certain terms have been used for brevity, clearness and understanding; but no unnecessary limitations are to be implied therefrom beyond the requirement of the prior art, because such terms are used for descriptive purposes and are intended to be broadly construed.

Moreover, the description and illustration of the invention is by way of example, and the scope of the invention is not limited to the exact details shown or described.

Having now described the features, discoveries and principles of the invention, the manner in which the improved floor mat system is constructed and used, the characteristics of the construction, and the advantageous, new and useful results obtained; the new and useful structures, devices, elements, arrangements, parts and combinations, are set forth in the appended claims.

5

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000